

SuSeFLAV: Supersymmetric particle spectrum and lepton flavor violation calculator

Technical Manual

April 27, 2011

Contents

1	SuSeFLAV/bsg.f	2
2	SuSeFLAV/ewsbiterate.f/coratmz	3
3	SuSeFLAV/ewsbiterate.f/RECURSIVE SUBROUTINE ITERATE	4
4	SuSeFLAV/ewsbiterate.f/REWSBCOR	6
5	SuSeFLAV/oneloopchargino.f	8
6	SuSeFLAV/oneloopfermion.f	10
7	SuSeFLAV/oneloophiggs.f/higgs_analytical	11
8	SuSeFLAV/oneloophiggs.f/pisisj	12
9	SuSeFLAV/oneloopneutralino.f	14
10	SuSeFLAV/oneloopselfenergy.f	16
11	SuSeFLAV/oneloopsfermion.f	18
12	SuSeFLAV/onelooptadpole.f	20
13	SuSeFLAV/rgeiterate.f	22

CONTENTS	2
14 SuSeFLAV/softspectrumb.f	25
15 SuSeFLAV/spectrumtl.f/completerun	27
16 SuSeFLAV/spectrumtl.f/runtomz	29
17 SuSeFLAV/SuSemain.f	30
18 susyflav/mssmrge.f	32
19 susyflav/smrge.f	35

1 SuSeFLAV/bsg.f

[Functions]

NAME:

subroutine bsg

SYNOPSIS:

Main routine for running SuSeFLAV.

FUNCTION:

This subroutine calculates the b->s,gamma rate
 The functions follow from that of Bertolini-Borzumati-Masiero
 And A. Bartl et. al (PRD 64 076009 (2001)).
 The SM NLO Contributions and MSSM LO Contributions are added.
 The functions are combinations of various functions presented
 in the papers above.

INPUTS:

tanbeta	-	ratio of vevs
mT	-	top quark mass
mB	-	bottom quark mass
Ceg	-	(1x2) Chargino eigen values
SUeg	-	(1x6) up-type squark eigenvalue
USU	-	(6x6) squark mixing matrix
OCL,OCR	-	(2 X 2) orthogonal matrices such that MChar = Transpose[OCR].Diag[MChar].OCL
mHchar	-	mass of charged higgs

RESULT:

Bbsg - b->s gamma decay rate

EXAMPLE:

```
subroutine bsg(tanbeta,mT,mB,Ceg,SUeg,USU,OCL,OCR,mHchar,Bbsg)
```

NOTES:

mHchar = Mass of the Charged Higgs Boson (NOT Squared !!)

BUGS:

SEE ALSO:

2 SuSeFLAV/ewsbiterate.f/coratmz

[*Functions*]

NAME:

SUBROUTINE coratmz

SYNOPSIS:

One loop correction to all standard model inputs at MZ.

FUNCTION:

Calculates one-loop threshold corrections to \$M_t\$, \$M_b\$, \$M_\tau\$, \$\alpha_{em}\$, \$\alpha_s\$ and \$\sin^2 \theta_w\$ at MZ.
We closely follow BPMZ [hep-ph/9606211].

INPUTS:

MW	- Mass of W boson.
MZ	- Mass of Z boson.
tanbeta	- the ratio of the vevs of the two Higgs doublet fields.
alphaDR	- \$\overline{\text{DR}}\$ Electromagnetic coupling constant.

RESULT:

MWc_mz	- One loop corrected mass of W boson.
MZc_mz	- One loop corrected mass of Z boson.
MTC_mz	- One loop corrected top quark mass. (Expand on correction parameters)
mBc_mz	- One loop corrected bottom quark mass.
mTau_c_mz	- One loop corrected tau lepton mass.
alphas1	- One loop corrected strong coupling constant.
alphaem	- One loop corrected electromagnetic coupling constant.
delalphaem	- One loop correction to electromagnetic coupling constant.
delalphas	- One loop correction to strong coupling constant.
sinsqtheff	- Corrected effective weak mixing angle.

EXAMPLE:

```
SUBROUTINE coratMZ(MW,MZ,tanbeta,alphaDR,MWc_mz, MZc_mz,MTc_mz,
$      mBc_mz,mTauc_mz,alphas1,alphaem,delalphas, delalphem,
$      sinsqtheff,newvev,mbdrbar,itcount)
```

NOTES:

Common blocks used in this routine

```
common/rgeopt_mz/mt_mz, mb_mz, mtau_mz
common/sminputs/ mbpole, mtaupole, Mtpole
common/higgsmixmz/ alphatree
common/sinsq_mz/sinsqthw_mz
common/mu_mz/ murgemz
common/qcd_cor/mbmzdrbar
common/softout_mat_mz/mSQRGz,mSURGz,mSDRGz,AURGz,ADRGz,
$      AERGz,ANURGz,mSLRGz,mSERGz, mSNURGz,ONz,OCLz,OCRz,
$      MCharz, MNeutz
common/rgeoutput_MZ/ mh1mzz,mh2mzz,M1tmz,M2tmz,M3tmz,
$      alph1MZ,alph2MZ,alph3MZ,vev1mz,vev2mz,yumz,ydmz,yemz
common/sparticles_MZ/SUeggz,SDeggz,SLeggz,SNeggz,Negz,Cegz,
$      mh0sqz,mhu0sqz,mhpmsqz,mA0sqz
```

External Subroutines used in this routine

```
EXTERNAL topcor, bottomcor, taucor,pizz, piww
EXTERNAL strongcoupling, emcoupling, vevwsb, S2ThetaW,
$      pizgamma,S2ThetaEff
```

BUGS:

SEE ALSO:

3 SuSeFLAV/ewsbiterate.f/RECURSIVE SUBROUTINE ITERATE

[*Functions*]

NAME:

Subroutine Iterate

SYNOPSIS:

Recursive subroutine for μ parameter minimization

FUNCTION:

This subroutine minimizes μ parameter using iterative methods and incorporates REWSB at msusy. Also, it checks for D-flat conditions and whether the determinant is negative.

INPUTS:

scale	- Scale at which minimization is done(ex. msusy or MZ)
mt	- One-loop corrected mass of top quark(GeV).
murge	- μ at tree level
msusy	- scale at which susy is broken.
newtbeta	- the ratio of the vevs of the twoHiggs doublet fields at msusy.

RESULT:

bmur	- $b_{\{\mu\}}$ obtained from converged value of μ
muflag	- flags unphysical μ . muflag = 2 for $\mu^2 < 0$ and if iteration count exceeds the limit.
try1	- Counter for iteration.
muold	- Converged/Minimized value of $ \mu $.
itcount	- Counter for RGE iteration.
flags	- Saves the error encountered in a character string.
mursq	- value of μ^2

EXAMPLE:

```
RECURSIVE SUBROUTINE ITERATE (scale,mt,murge,bmur,newtbeta,
$      msusy,muflag,try1,muold,itcount,flags, mursq)
```

NOTES:

Common Blocks used:

```
common/mssminputs/ m0, m12, m10, m20, sgnmu, tanbeta, a0
common/softout_mat/mSQRG,mSURG,mSDRG,AURG,ADRG,
$      AERG,ANURG,mSLRG,mSERG, mSNURG,ON,OCL,OCR,MChar, MNeut
common/rgeoutput_susy/ mh1mz,mh2mz,M1tz,M2tz,M3tz,
$      alph1,alph2,alph3,vev1,vev2,yuRG,ydRG,yeRG
```

```

common/sparticles_susy/SUegg,SDegg,SLegg,SNegg,Neg,Ceg,
$      mh0sq,mhu0sq,mhpmsq,mA0sq
common/sminputs/ mbpole, mtaupole, Mtpole
common/sinsq_susy/sinsqthw_susy
common/hzV/ delta1,delta2

External routines used in this routine:
EXTERNAL pizz,tadpole1,piww
EXTERNAL tadpole2,pis1s1,pis1s2,pis2s2

```

BUGS:

SEE ALSO:

4 SuSeFLAV/ewsbiterate.f/REWSBCOR[*Functions*]**NAME:**

Subroutine REWSBCOR

SYNOPSIS:

One loop correction to all MSSM paramters at msusy.

FUNCTION:

Calculates complete one-loop threshold corrections to all MSSM particles.
 We closely follow BPMZ [hep-ph/9606211].

INPUTS:

<i>mur</i>	- Converged value of \mu parameter.
<i>bmur</i>	- Converged value of b_{\mu} parameter.
<i>sgnmu</i>	- Sign of \mu parameter.
<i>newtbeta</i>	- \tan\beta at msusy scale.
<i>MT</i>	- One-loop corrected mass of top quark (GeV).
<i>msusy</i>	- Susy breaking scale (GeV).

RESULT:

Corrected sfermions, gauginos and higgs masses.

M3t	- One-loop corrected gluino mass(GeV).
mAm3	- One-loop corrected psuedo scalar higgs mass(GeV).
STeg	- (1 X 2) One-loop corrected (s)top masses, contains mixed state of L and R.
SCeg	- (1 X 2) One-loop corrected (s)charm masses, L and R components.
SUqeg	- (1 X 2) One-loop corrected (s)up masses, L and R components.
SBeg	- (1 X 2) One-loop corrected (s)bottom masses, contains mixed state of L and R.
SSTeg	- (1 X 2) One-loop corrected (s)strange masses, L and R components.
SDneg	- (1 X 2) One-loop corrected (s)down masses, L and R components.
STaueg	- (1 X 2) One-loop corrected (s)tau masses, contains mixed state of L and R.
SMUeg	- (1 X 2) One-loop corrected (s)mu masses, L and R components.
SEeg	- (1 X 2) One-loop corrected (s)electron masses, L and R components.
tsnu	- One-loop corrected tau (s)neutrino mass.
musnu	- One-loop corrected mu (s)neutrino mass.
elsnu	- One-loop corrected electron (s)neutrino mass.
newmA0sq	one loop corrected higgs masses.
newmh0sq	Currently we use compact analytical expression at two-loop level for the lightest
newmhpmqsq	Heinenmeyer, Hollik and Weiglein [hep-ph/ 9903404]
newmHu0sq	
Cegm	- (1 X 2) One-loop corrected chargino masses.
negm	- (1 X 4) One-loop corrected neutralino masses.

EXAMPLE:

```
SUBROUTINE REWSBCOR(mur,bmur,sgnmu,newtbeta,MT,
$      msusy,msnew,M3t,mAm3,
$      STeg,SCeg,SUqeg,SBeg,SSTeg,SDneg,STaueg,SMUeg,SEeg,
$      tsnu,musnu,elsnu, newmA0sq, newmh0sq, newmhpmqsq,
$      newmHu0sq,Cegm,negm,itcount)
```

NOTES:

Common blocks used in this routine:

```
common/sminputs/ mbpole, mtaupole, Mtpole
common/softout_mat/mSQRG,mSURG,mSDRG,AURG,ADRG,
$      AERG,ANURG,mSLRG,mSERG, mSNURG,ON,OCL,OCR,MChar, MNeut
common/rgeoutput_susy/ mh1mz,mh2mz,M1tz,M2tz,M3tz,
$      alph1,alph2,alph3,vev1,vev2,yuRG,ydRG,yeRG
common/sparticles_susy/SUegg,SDegg,SLegg,SNegg,Neg,Ceg,
$      mh0sq,mhu0sq,mhpmsq,mA0sq
common/sinsq_susy/sinsqthw_susy
common/opt_mixing/OCRm, OCLTm,ONew, alpha
```

```
common/vev_ewsb/ vev1n,vev2n
```

External subroutines in this routine:

```
EXTERNAL pizz,tadpole1,piww
EXTERNAL tadpole2,piaa,veviewsb,pis1s1,pis1s2,pis2s2,pihphm,pistop
EXTERNAL pisbottom,pischarm,pisupq,pistaul
EXTERNAL pisdown,pistausnu,higgs_analytical
```

BUGS:

SEE ALSO:

5 SuSeFLAV/oneloopchargino.f

[*Functions*]

NAME:

subroutine chargino

SYNOPSIS:

One loop correction to chargino.

FUNCTION:

Computes 1loop correction to charginos at a given energy scale and external momenta

INPUTS:

p	- External momentum
q	- Energy scale
g, gp, g3	- Gauge couplings(g = em, gp = weak, g3 = strong)
mt, mb, mtau	- pole masses of top, bottom and tau
mSQRG, mSDRG, mSURG, mSLRG, mSERG	- (3 X 3) mass matrix definition
yURG, ydRG, yeRG	- (3 X 3) Yukawas

```

AURG,ADRG,AERG          - (3 X 3)Trilinear couplings
pizzT,piwwt              - self energy of W and Z bosons at M_z
mh0sq,mhu0sq,mhpmsq,mA0sq - physiccal higgs mass squared
modmu                     - modulus of the \mu paramter
vev1,vev2                 - vacuum expectation values of the two
                           higgs doublet fields
M3t                       - Gaugino mass at msusy
tanbeta                   - the ratio of the vevs of the
                           two Higgs doublet fields.

SUegg = 6 eigenvalues of UP-Squark mass matrix.
SDegg = 6 eigenvalues of Down-Squark mass matrix.
Slegg = 6 eigenvalues of slepton mass matrix.
SNegg = 3 eigenvalues of sneutrino mass matrix.
ON   = (4 X 4) orthogonal matrix such that
      ON.MNeut.Transpose[ON] = Diag[MNeut]
Neg   = 4 singular values (descending order) of the
      Neutralino mass matrix.

OCR, OCL = (2 X 2) orthogonal matrices such that
            MChar = Transpose[OCR].Diag[MChar].OCL
Ceg   = 2 singular values of the chargino Mass Matrix

```

RESULT:

```

Cegm      = 2 eigenvalues of the 1-loop corrected chargino mass matrix.
OCRm, OCLTm = (2 X 2) orthogonal matrices such that
              MChar = Transpose[OCRm].Diag[MChar].OCLTm
charmasstot = (2x2) corrected chargino mass matrix

```

EXAMPLE:

```

subroutine chargino(p,q,g,qp,mt,mb,mtau,tanbeta,mSQRG,mSDRG,mSURG,
$      mSLRG,mSERG,AURG,ADRG,AERG,yuRG,ydRG,yeRG,SUegg,SDegg,SLegg,
$      SNegg,Neg,Ceg,MChar,ON,OCL,OCR,modmu,mh0sq,mhu0sq,mhpmsq,
$      mA0sq,vev1,vev2,charmasstot,OCRm,OCLTm,Cegm)

```

NOTES:

1. q, the energy scale at which the corrections are added = msusy.
2. Conventions and notations followed are that of BPMZ.
3. p = msusy

BUGS:

SEE ALSO:

6 SuSeFLAV/oneloopfermion.f

[Functions]

NAME:

Subroutine topcor, bottomcor and taucor

SYNOPSIS:

One loop correction to fermions.

FUNCTION:

Computes self energy for third generation fermions at a given energy scale and external momenta

INPUTS:

p	- External momentum
q	- Energy scale
g, gp, g3	- Gauge couplings(g = em, gp = weak, g3 = strong)
mt, mb, mtau	- pole masses of top, bottom and tau
mSQRG, mSDRG, mSURG, mSLRG, mSERG	- (2 X 2) mass matrix definition
yURG, ydRG, yeRG	- Yukawas
AURG, ADRG, AERG	- Trilinear couplings
pizzT, piwwT	- self energy of W and Z bosons at M_z
mh0sq, mhu0sq, mhpmssq, mA0sq	- physiccal higgs mass squared
modmu	- modulus of the \mu paramter
M3t, M2t	- Gaugino mass at msusy
tanbeta	- the ratio of the vevs of the twoHiggs doublet fields.
SUegg	= 6 eigenvalues (ascending order) of UP-Squark mass matrix.
SDegg	= 6 eigenvalues (ascending order) of Down-Squark mass matrix.
Slegg	= 6 eigenvalues (ascending order) of slepton mass matrix.
SNegg	= 3 eigenvalues (ascending order) of sneutrino mass matrix.
ON	= (4 X 4) orthogonal matrix such that ON.MNeut.Transpose[ON] = Diag[MNeut]
Neg	= 4 singular values (descending order) of the Neutralino mass matrix.
OCR, OCL	= (2 X 2) orthogonal matrices such that MChar = Transpose[OCR].Diag[MChar].OCL
Ceg	= 2 singular values of the Neutralino Mass Matrix

RESULT:

S_eg = 2 eigenvalues of the corrected mass matrix(L and R components).

EXAMPLE:

```

SUBROUTINE topcor(p,q,g,g3,M3t,mt,mb,mtau,tanbeta,mSQRG,mSDRG,
$      mSURG,mS1RG,mSERG,AURG,ADRG,AERG,yuRG,ydRG,yeRG,SUegg,SDegg,
$      SLegg,SNegg,Neg,Ceg,mh0sq,mhu0sq,mhpmsq,mA0sq,modmu,ON,OCL,
$      OCR,correction)

SUBROUTINE bottomcor(p,q,g,g3,M3t,mt,mb,mtau,tanbeta,mSQRG,mSDRG,
$      mSURG,mS1RG,mSERG,AURG,ADRG,AERG,yuRG,ydRG,yeRG,SUegg,SDegg,
$      SLegg,SNegg,Neg,Ceg,mh0sq,mhu0sq,mhpmsq,mA0sq,modmu,ON,OCL,
$      OCR,hb,htau,M2tz,mbcor)

SUBROUTINE taukor(p,q,g,g3,M3t,mt,mb,mtau,tanbeta,mSQRG,mSDRG,
$      mSURG,mS1RG,mSERG,AURG,ADRG,AERG,yuRG,ydRG,yeRG,SUegg,SDegg,
$      SLegg,SNegg,Neg,Ceg,mh0sq,mhu0sq,mhpmsq,mA0sq,modmu,ON,OCL,
$      OCR,M2tz,mtaukor)

```

NOTES:

1. q, the energy scale at which the corrections are added = MZ
2. Conventions and notations followed are that of BPMZ.

BUGS:

SEE ALSO:

7 SuSeFLAV/oneloophiggs.f/higgs_analytical

[*Functions*]

NAME:

subroutine higgs_analytical

SYNOPSIS:

Computes One loop correction(analytical) to cp even higgs boson and light higgs.

FUNCTION:

The routine calculates one loop correction to cp even higgs boson.
 hep-ph/ 9903404, hep-ph/0002213 - analytical expression for light higgs and
 CP- even higgs

INPUTS:

alph3	- $g^3/(16 * \pi^2)$
mt	- running masses of top, bottom and tau
yuRG,ydRG,yeRG	- (3 X 3) Yukawas
AURG	- (3 X 3) Trilinear couplings
pizzT,piwwT	- self energy of W and Z bosons at M_Z
modmu	- modulus of the μ parameter
vev1,vev2	- vacuum expectation values of the two higgs doublet fields
M3t	- Gaugino mass at msusy
tanbeta	- the ratio of the vevs of the two Higgs doublet fields.
SUegg = 6 eigenvalues of UP-Squark mass matrix.	

RESULT:

sigphi1,sigphi2,	
sigphi12,sig2phi2	
sig2phi2yuk	- elements of One loop corrections.

EXAMPLE:

```
SUBROUTINE higgs_analytical(MT,tanbeta,SUegg,AURG,sgnmu,modmu,
$      pizzT,piwwT,alph3,sigphi1,sigphi2,
$      sigphi12,sig2phi2,sig2phi2yuk)
```

NOTES:

1. q, the energy scale at which the corrections are added = msusy.
2. Conventions and notations followed are that of BPMZ.

BUGS:

SEE ALSO:**8 SuSeFLAV/oneloophiggs.f/pisisj**

[*Functions*]

NAME:

```
subroutine pis1s1,pis1s2,pis2s2
```

SYNOPSIS:

Computes One loop correction to cp even higgs boson.

FUNCTION:

The routine calcutes one loop correction to cp even higgs boson.
From hep-ph/9606211's appendix.

INPUTS:

p	- External momentum
q	- Energy scale
g, gp, g3	- Gauge couplings(g = em, gp = weak, g3 = strong)
mt, mb, mtau	- pole masses of top, bottom and tau
mSQRG, mSDRG, mSURG, mSLRG, mSERG	- (3 X 3) mass matrix definition
yURG, ydRG, yeRG	- (3 X 3) Yukawas
AURG, ADRG, AERG	- (3 X 3) Trilinear couplings
pizzT, piwwT	- self energy of W and Z bosons at M_z
mh0sq, mhu0sq, mhpmssq, mA0sq	- physical higgs mass squared
modmu	- modulus of the \mu paramter
vev1, vev2	- vacuum expectation values of the two higgs doublet fields
M3t	- Gaugino mass at msusy
tanbeta	- the ratio of the vevs of the two Higgs doublet fields.
SUegg	= 6 eigenvalues of UP-Squark mass matrix.
SDegg	= 6 eigenvalues of Down-Squark mass matrix.
Slegg	= 6 eigenvalues of slepton mass matrix.
SNegg	= 3 eigenvalues of sneutrino mass matrix.
ON	= (4 X 4) orthogonal matrix such that ON.MNeut.Transpose[ON] = Diag[MNeut]
Neg	= 4 singular values (descending order) of the Neutralino mass matrix.
OCR, OCL	= (2 X 2) orthogonal matrices such that MChar = Transpose[OCR].Diag[MChar].OCL
Ceg	= 2 singular values of the chargino Mass Matrix

RESULT:

```
pis1s1,pis1s2,pis2s2 = one loop correction at a given
scale(generally msusy).
```

EXAMPLE:

```
subroutine pis1s1(p,q,g,qp,mt,mb,mtau,tanbeta,mSQRG,mSDRG,mSURG,
$      mSLRG,mSERG,AURG,ADRG,AERG,yuRG,ydRG,yeRg,SUegg,SDegg,SLegg,
$      SNegg,Neg,Ceg,ON,OCL,OCR,sgnmu,modmu,mh0sq,mhu0sq,mHpmsq,
$      mA0sq,vev1,vev2,pis1s1ans)

subroutine pis1s2(p,q,g,qp,mt,mb,mtau,tanbeta,mSQRG,mSDRG,mSURG,
$      mSLRG,mSERG,AURG,ADRG,AERG,yuRG,ydRG,yeRg,SUegg,SDegg,SLegg,
$      SNegg,Neg,Ceg,ON,OCL,OCR,sgnmu,modmu,mh0sq,mhu0sq,
$      mHpmsq,mA0sq,vev1,vev2,pis1s2ans)

subroutine pis2s2(p,q,g,qp,mt,mb,mtau,tanbeta,mSQRG,mSDRG,mSURG,
$      mSLRG,mSERG,AURG,ADRG,AERG,yuRG,ydRG,yeRg,SUegg,SDegg,SLegg,
$      SNegg,Neg,Ceg,ON,OCL,OCR,sgnmu,modmu,mh0sq,mhu0sq,mHpmsq,
$      mA0sq,vev1,vev2,pis2s2ans)
```

NOTES:

1. q, the energy scale at which the corrections are added = msusy.
2. Conventions and notations followed are that of BPMZ.

BUGS:

SEE ALSO:**9 SuSeFLAV/oneloopneutralino.f**

[*Functions*]

NAME:

```
subroutine neutralino
```

SYNOPSIS:

One loop correction to neutralino.

FUNCTION:

Computes 1-loop correction to neutralinos at a given energy scale and external momenta

INPUTS:

p	- External momentum
q	- Energy scale
g, gp, g3	- Gauge couplings(g = em, gp = weak, g3 = strong)
mt, mb, mtau	- pole masses of top, bottom and tau
mSQRG, mSDRG, mSURG, mSLRG, mSERG	- (3 X 3) mass matrix definition
yURG, ydRG, yeRG	- (3 X 3) Yukawas
AURG, ADRG, AERG	- (3 X 3) Trilinear couplings
pizzT, piwwT	- self energy of W and Z bosons at M_z
mh0sq, mhu0sq, mhpmssq, mA0sq	- physical higgs mass squared
modmu	- modulus of the \mu parameter
vev1, vev2	- vacuum expectation values of the two higgs doublet fields
M3t	- Gaugino mass at msusy
tanbeta	- the ratio of the vevs of the two Higgs doublet fields.
SUegg	= 6 eigenvalues of UP-Squark mass matrix.
SDegg	= 6 eigenvalues of Down-Squark mass matrix.
Slegg	= 6 eigenvalues of slepton mass matrix.
SNegg	= 3 eigenvalues of sneutrino mass matrix.
ON	= (4 X 4) orthogonal matrix such that ON.MNeut.Transpose[ON] = Diag[MNeut]
Neg	= 4 singular values (descending order) of the Neutralino mass matrix.
OCR, OCL	= (2 X 2) orthogonal matrices such that MChar = Transpose[OCR].Diag[MChar].OCL
Ceg	= 2 singular values of the chargino Mass Matrix

RESULT:

Negm	= 4 eigenvalues of the 1-loop corrected neutralino mass matrix.
ONew	= (4 X 4) corrected orthogonal matrix such that MChar = Transpose[OneW].Diag[MNeut].ONew
neutmassmasstot	= (4x4) corrected neutralino mass matrix

EXAMPLE:

```
subroutine neutralino(p,q,g, gp, mt, mb, mtau, tanbeta, mSQRG, mSDRG,
```

```
$      mSURG,mSLRG,mSERG,AURG,ADRG,AERG,yuRG,ydRG,yeRG,SUegg,SDegg,
$      SLegg,SNegg, MNeut1,Neg,Ceg,ON,OCL,OCR,modmu,mh0sq,mhu0sq,
$      mHpmgsq, mA0sq, vev1, vev2, ONew, Negm, neutmasstot)
```

NOTES:

1. q, the energy scale at which the corrections are added = msusy.
2. Conventions and notations followed are that of BPMZ.
3. p = msusy

BUGS:

SEE ALSO:**10 SuSeFLAV/oneloopselfenergy.f**

[*Functions*]

NAME:

oneloopselfenergy

SYNOPSIS:

One loop correction to Z,W,hA,Hpm.

FUNCTION:

Computes self energy for W,Z,hA and Hpm, given, energy scale and external momenta

INPUTS:

p	- External momentum
q	- Energy scale
g, gp, g3	- Gauge couplings(g = em, gp = weak, g3 = strong)
mt, mb, mtau	- pole masses of top, bottom and tau
mSQRG, mSDRG, mSURG, mSLRG, mSERG	- (2 X 2) mass matrix definition
AURG, ADRG, AERG	- Trilinear couplings
mh0sq, mhu0sq, mhpmsq, mA0sq	- physical higgs mass squared
modmu	- modulus of the \mu paramter
tanbeta	- the ratio of the vevs of the two Higgs doublet fields.

```

SUegg      = 6 eigenvalues (ascending order) of UP-Squark mass matrix.
SDegg      = 6 eigenvalues (ascending order) of Down-Squark mass matrix.
Slegg      = 6 eigenvalues (ascending order) of slepton mass matrix.
SNegg      = 3 eigenvalues (ascending order) of sneutrino mass matrix.
ON         = (4 X 4) orthogonal matrix such that
              ON.MNeut.Transpose[ON] = Diag[MNeut]
Neg        = 4 singular values (descending order) of the Neutralino mass matrix.

OCR, OCL = (2 X 2) orthogonal matrices such that
              MChar = Transpose[OCR].Diag[MChar].OCL
Ceg        = 2 singular values of the Neutralino Mass Matrix

```

RESULT:

```

pizzT      - Z boson self energy
piwwT      - W boson self energy
piaaT      - Higgs boson A self energy
piHphm     - Charged higgs H+ self energy

```

EXAMPLE:

```

SUBROUTINE pizz(p,q,g,mt(mb,mtau,tanbeta,mSQRG,mSDRG,mSURG,mSLRG,
$      mSERG,AURG,ADRG,AERG,SUegg,SDegg,Slegg,SNegg,Neg,Ceg,mh0sq,
$      mhu0sq,mhpmsq,mA0sq,modmu,ON,OCL,OCR,pizzT)

SUBROUTINE piww(p,q,g,mt(mb,mtau,tanbeta,mSQRG,mSDRG,mSURG,mSLRG,
$      mSERG,AURG,ADRG,AERG,SUegg,SDegg,Slegg,SNegg,Neg,Ceg,mh0sq,
$      mhu0sq,mhpmsq,mA0sq,modmu,ON,OCL,OCR,piwwT)

SUBROUTINE piaa(p,q,g,gp,mt(mb,mtau,tanbeta,mSQRG,mSDRG,mSURG,
$      mSLRG,mSERG,yuRG,ydRG,yeRG,AURG,ADRG,AERG,SUegg,SDegg,Slegg,
$      SNegg,Neg,Ceg,mh0sq,mhu0sq,mhpmsq,mA0sq,modmu,ON,OCL,OCR,
$      piaaT)

SUBROUTINE pihphm(p,q,g,gp,mt(mb,mtau,tanbeta,mSQRG,mSDRG,mSURG,
$      mSLRG,mSERG,AURG,ADRG,AERG,SUegg,SDegg,Slegg,SNegg,Neg,Ceg,
$      yuRG,yeRG,ydRG,mh0sq,mhu0sq,mhpmsq,mA0sq,modmu,ON,OCL,OCR,
$      pihphmT)

```

NOTES:

1. q, the energy scale at which the corrections are added = MZ for W and Z bosons.
2. Running values of gauge couplings(Rge output) are used.
3. Pole masses: DRbar scheme is followed.
4. Conventions followed are that of BPMZ.

BUGS:

SEE ALSO:

11 SuSeFLAV/oneloopsfermion.f

[*Functions*]

NAME:

oneloopsfermion

SYNOPSIS:

One loop correction to sfermions.

FUNCTION:

Computes self energy for all sfermions at a given energy scale and external momenta

INPUTS:

p	- External momentum
q	- Energy scale
g, gp, g3	- Gauge couplings(g = em, gp = weak, g3 = strong)
mt, mb, mtau	- pole masses of top, bottom and tau
mSQRG, mSDRG, mSURG, mSLRG, mSERG	- (3 X 3) mass matrix definition
yURG, ydRG, yeRG	- (3 X 3) Yukawas
AURG, ADRG, AERG	- (3 X 3) Trilinear couplings
pizzT, piwwT	- self energy of W and Z bosons at M_Z
mh0sq, mhu0sq, mhpmsq, mA0sq	- physicsal higgs mass squared
modmu	- modulus of the \mu paramter
vev1, vev2	- vacuum expectation values of the two higgs doublet fields
M3t	- Gaugino mass at msusy
tanbeta	- the ratio of the vevs of the twoHiggs doublet fields.
SUegg	= 6 eigenvalues of UP-Squark mass matrix.
SDegg	= 6 eigenvalues of Down-Squark mass matrix.

```

Slegg = 6 eigenvalues of slepton mass matrix.
SNegg = 3 eigenvalues of sneutrino mass matrix.
ON    = (4 X 4) orthogonal matrix such that
        ON.MNeutTranspose[ON] = Diag[MNeut]
Neg   = 4 singular values (descending order) of the
        Neutralino mass matrix.

OCR, OCL = (2 X 2) orthogonal matrices such that
            MChar = Transpose[OCR].Diag[MChar].OCL
Ceg    = 2 singular values of the chargino Mass Matrix

```

RESULT:

```
S_eg     = 2 eigenvalues of the corrected mass matrix( L and R components).
```

EXAMPLE:

```

SUBROUTINE pistop(p,q,g, gp, g3, mt, mb, mtau, tanbeta, mSQRG, mSDRG,
$      mSURG, mSLRG, mSERG, yuRG, ydRG, yeRG, AURG, ADRG, AERG, SUegg, SDegg,
$      SLegg, SNegg, Neg, Ceg, pizzT, piwwT, mh0sq, mhu0sq, mhpmsq, mA0sq,
$      modmu, ON, OCL, OCR, vev1, vev2, M3t, STeg)

SUBROUTINE pisbottom(p, q, g, gp, g3, mt, mb, mtau, tanbeta, mSQRG, mSDRG,
$      mSURG, mSLRG, mSERG, yuRG, ydRG, yeRG, AURG, ADRG, AERG, SUegg, SDegg,
$      SLegg, SNegg, Neg, Ceg, pizzT, piwwT, mh0sq, mhu0sq, mhpmsq, mA0sq,
$      modmu, ON, OCL, OCR, vev1, vev2, M3t, SBeg)

SUBROUTINE pisstrange(p, q, g, gp, g3, mt, mb, mtau, tanbeta, mSQRG, mSDRG,
$      mSURG, mSLRG, mSERG, yuRG, ydRG, yeRG, AURG, ADRG, AERG, SUegg, SDegg,
$      SLegg, SNegg, Neg, Ceg, pizzT, piwwT, mh0sq, mhu0sq, mhpmsq, mA0sq,
$      modmu, ON, OCL, OCR, vev1, vev2, M3t, SSTeg)

SUBROUTINE pisdown(p, q, g, gp, g3, mt, mb, mtau, tanbeta, mSQRG, mSDRG,
$      mSURG, mSLRG, mSERG, yuRG, ydRG, yeRG, AURG, ADRG, AERG, SUegg, SDegg,
$      SLegg, SNegg, Neg, Ceg, pizzT, piwwT, mh0sq, mhu0sq, mhpmsq, mA0sq,
$      modmu, ON, OCL, OCR, vev1, vev2, M3t, SDeg)

SUBROUTINE pischarm(p, q, g, gp, g3, mt, mb, mtau, tanbeta, mSQRG, mSDRG,
$      mSURG, mSLRG, mSERG, yuRG, ydRG, yeRG, AURG, ADRG, AERG, SUegg, SDegg,
$      SLegg, SNegg, Neg, Ceg, pizzT, piwwT, mh0sq, mhu0sq, mhpmsq, mA0sq,
$      modmu, ON, OCL, OCR, vev1, vev2, M3t, SCeg)

SUBROUTINE pisupq(p, q, g, gp, g3, mt, mb, mtau, tanbeta, mSQRG, mSDRG,
$      mSURG, mSLRG, mSERG, yuRG, ydRG, yeRG, AURG, ADRG, AERG, SUegg, SDegg,
$      SLegg, SNegg, Neg, Ceg, pizzT, piwwT, mh0sq, mhu0sq, mhpmsq, mA0sq,
$      modmu, ON, OCL, OCR, vev1, vev2, M3t, SUeg)

```

```

SUBROUTINE pistaul(p,q,g, gp, g3, mt, mb, mtau, tanbeta, mSQRG, mSDRG,
$      mSURG, mSLRG, mSERG, yuRG, ydRG, yeRG, AURG, ADRG, AERG, SUegg, SDegg,
$      SLegg, SNegg, Neg, Ceg, pizzT, piwwT, mh0sq, mhu0sq, mhpmsq, mA0sq,
$      modmu, ON, OCL, OCR, vev1, vev2, M3t, STaueg)

SUBROUTINE pisMUL(p, q, g, gp, g3, mt, mb, mtau, tanbeta, mSQRG, mSDRG,
$      mSURG, mSLRG, mSERG, yuRG, ydRG, yeRG, AURG, ADRG, AERG, SUegg, SDegg,
$      SLegg, SNegg, Neg, Ceg, pizzT, piwwT, mh0sq, mhu0sq, mhpmsq, mA0sq,
$      modmu, ON, OCL, OCR, vev1, vev2, M3t, SMueg)

SUBROUTINE pitausnu(p, q, g, gp, g3, mt, mb, mtau, tanbeta, mSQRG, mSDRG,
$      mSURG, mSLRG, mSERG, yuRG, ydRG, yeRG, AURG, ADRG, AERG, SUegg, SDegg,
$      SLegg, SNegg, Neg, Ceg, pizzT, piwwT, mh0sq, mhu0sq, mhpmsq, mA0sq,
$      modmu, ON, OCL, OCR, vev1, vev2, M3t, tsnu)

SUBROUTINE pimulsnu(p, q, g, gp, g3, mt, mb, mtau, tanbeta, mSQRG, mSDRG,
$      mSURG, mSLRG, mSERG, yuRG, ydRG, yeRG, AURG, ADRG, AERG, SUegg, SDegg,
$      SLegg, SNegg, Neg, Ceg, pizzT, piwwT, mh0sq, mhu0sq, mhpmsq, mA0sq,
$      modmu, ON, OCL, OCR, vev1, vev2, M3t, musnu)

SUBROUTINE pielsnu(p, q, g, gp, g3, mt, mb, mtau, tanbeta, mSQRG, mSDRG,
$      mSURG, mSLRG, mSERG, yuRG, ydRG, yeRG, AURG, ADRG, AERG, SUegg, SDegg,
$      SLegg, SNegg, Neg, Ceg, pizzT, piwwT, mh0sq, mhu0sq, mhpmsq, mA0sq,
$      modmu, ON, OCL, OCR, vev1, vev2, M3t, elsnu)

```

NOTES:

1. q, the energy scale at which the corrections are added = msusy.
2. Running values of gauge couplings(Rge output) are used.
3. Pole masses: DRbar scheme is followed.
4. Conventions and notations followed are that of BPMZ.

BUGS:

SEE ALSO:

DSYEV - Diagonalizing Routine.
LAPACK

12 SuSeFLAV/oneloopadpole.f

[Functions]

NAME:

```
subroutine tadpole1,tadpole2
```

SYNOPSIS:

Computes One loop tadpoles.

FUNCTION:

The routine calculates one loop tadpoles
 From hep-ph/9606211's appendix. It should be done at MSusy to minimize the
 1-loop contributions.

INPUTS:

p	- External momentum
q	- Energy scale
g, gp, g3	- Gauge couplings(g = em, gp = weak, g3 = strong)
mt, mb, mtau	- pole masses of top, bottom and tau
mSQRG, mSDRG, mSURG, mSLRG, mSERG	- (3 X 3) mass matrix definition
yURG, ydRG, yeRG	- (3 X 3) Yukawas
AURG, ADRG, AERG	- (3 X 3) Trilinear couplings
pizzT, piwwT	- self energy of W and Z bosons at M_z
mh0sq, mhu0sq, mhpmssq, mA0sq	- physical higgs mass squared
modmu	- modulus of the \mu paramter
vev1, vev2	- vacuum expectation values of the two higgs doublet fields
M3t	- Gaugino mass at msusy
tanbeta	- the ratio of the vevs of the two Higgs doublet fields.
SUegg	= 6 eigenvalues of UP-Squark mass matrix.
SDegg	= 6 eigenvalues of Down-Squark mass matrix.
Slegg	= 6 eigenvalues of slepton mass matrix.
SNegg	= 3 eigenvalues of sneutrino mass matrix.
ON	= (4 X 4) orthogonal matrix such that ON.MNeut.Transpose[ON] = Diag[MNeut]
Neg	= 4 singular values (descending order) of the Neutralino mass matrix.
OCR, OCL	= (2 X 2) orthogonal matrices such that MChar = Transpose[OCR].Diag[MChar].OCL
Ceg	= 2 singular values of the chargino Mass Matrix

RESULT:

```
delta1,delta2 = tadpoles at a given scale(generally msusy).
```

EXAMPLE:

```
subroutine tadpole1(q,g,mt(mb,mtau,tanbeta,mSQRG,mSDRG,mSURG,
$      mSLRG,mSERG,AURG,ADRG,AERG,yuRG,ydRG,yeRG,SUegg,SDegg,SLegg,
$      SNegg,Neg,Ceg,ON,OCL,OCR,sgnmu,modmu,mh0sq,mhu0sq,mHpmgsq,
$      mA0sq,vev1,vev2,pizzT,piwwT,delta1)

subroutine tadpole2(q,g,mt(mb,mtau,tanbeta,mSQRG,mSDRG,mSURG,
$      mSLRG,mSERG,AURG,ADRG,AERG,yuRG,ydRG,yeRG,SUegg,SDegg,SLegg,
$      SNegg,Neg,Ceg,ON,OCL,OCR,sgnmu,modmu,mh0sq,mhu0sq,mHpmgsq,
$      mA0sq,vev1,vev2,pizzT,piwwT,delta2)
```

NOTES:

1. q, the energy scale at which the corrections are added = msusy.
2. Conventions and notations followed are that of BPMZ.

BUGS:

SEE ALSO:**13 SuSeFLAV/rgeiterate.f**

[*Functions*]

NAME:

RECURSIVE Subroutine rgeiterate

SYNOPSIS:

Run mssm and sm RGEs, computes tree level physical masses
and the corresponding one loop correction
for MSSM parameters.

FUNCTION:

This suborutine integrates MSSM RGEs and computes low
energy spectrum at msusy.

INPUTS:

MW	- Mass of W boson
MZ	- Mass of Z boson
MT	- top quark mass in \overline{DR} scheme
mb	- bottom quark mass in \overline{DR} scheme
mtau	- \tau lepton mass in \overline{DR} scheme
msusyold	- Initial guess value of msusy = sqrt(m0^2 + 4 m12^2)
vevsc	- scaled vev. vev/root2
vevin	- vev at MZ
yuin	- (3x3) up type yukawa matrix
ydin	- (3x3) down type yukawa matrix
yein	- (3x3) matrix yukawa for leptons
alphaDR	- alpha_{\overline{DR}}
alph1in	- g1^2/(16 pi^2) at MZ
alph2in	- g2^2/(16 pi^2) at MZ
alph3in	- g3^2/(16 pi^2) at MZ
mur	- \mu at mz
bmur	- \bmu at mz
msusy	- susy breaking scale
prnstat	- Print control
itcount	- Rge iteration count

RESULT:

MTc_mz	- one loop correction to top quark
mBc_mz	- one loop correction to bottom quark
mtauc_mz	- one loop correction to tau lepton
delalphem	- one loop correction to em coupling
delalphas	- one loop correction to strong coupling
murge	- RGE output: \mu at M_{susy} scale
bmerge	- RGE output: b_\mu at M_{susy} scale
newtbeta	- Ratio of vev at msusy from rge running.
msusynew	- geometric mean of stop1 and stop2
flags	- flags problem with rge running, if any.
itcount	- iteration count
stopratu	
stopratd	- variables used to check for global convergence of \mu
sinsqtheff	- one loop corrected effective sinsqthw

Calculated tree level and 1-loop masses are stored in common blocks

EXAMPLE:

```
RECURSIVE SUBROUTINE rgeit(MW,MZ,MT,MTc_mz,mB,mBc_mz,mTau,
```

```
$      mtauc_mz,msusyold,vevsc,vevin,vev1in,vev2in,yuin,
$      ydin,yein,alphaDR,alph1in,alph2in,delalphem,
$      alph3in,delalphas,mur,bmur,murge,prnstat,check,
$      newtbeta, MTatMZ,msusynew,mursq,try,newmh0sq,cheg,
$      flags,runum,itcount,stopratu,stopratd,sinsqtheff)
```

NOTES:

Common Blocks used:

```
common/mascorr/ MT_qcd_corr
common/sminputs/ mbpole, mtaupole, Mtpole
common/loops/ lopt,rhn
common/mssminputs/ m0, m12, m10, m20, sgnmu, tanbeta, a0
common/mssmrhn/ MR1,MR2,MR3,ue3, Ynui
common/charinputs/case, model
common/rgeinput_high/ MX, M1X,M2X,M3X,mh10,mh20,
$      mQ0,mU0,mD0,mE0,mL0,mNU0
common/softout_mat/mSQRG,mSURG,mSDRG,AURG,ADRG,
$      AERG,ANURG,mSLRG,mSERG, mSNURG,ON,OCL,OCR,MChar, MNeut
common/softout_mat_mz/mSQRGz,mSURGz,mSDRGz,AURGz,ADRGz,
$      AERGz,ANURGz,mSLRGz,mSERGz, mSNURGz,ONz,OCLz,OCRz,
$      MCharz, MNeutz
common/rgeoutput_susy/ mh1mz,mh2mz,M1tz,M2tz,M3tz,
$      alph1,alph2,alph3,vev1,vev2,yuRG,ydRG,yeRG
common/rgeoutput_MZ/ mh1mzz,mh2mzz,M1tmz,M2tmz,M3tmz,
$      alph1MZ,alph2MZ,alph3MZ,vev1mz,vev2mz,yumz,ydmz,yemz
common/sparticles_susy/SUegg,SDegg,SLegg,SNegg,Neg,Ceg,
$      mh0sq,mhu0sq,mhpmsq,ma0sq
common/sparticles_MZ/SUeggz,SDeggz,SLeggz,SNeggz,Negz,Cegz,
$      mh0sqz,mhu0sqz,mhpmsqz,ma0sqz
common/soft_mat_susy/ mSL1, SLeg, USL, SNeg, USN, SUeg, USU,
$      SDeg, USD
common/soft_mat_mz/ mSL1z, SLegz, USLz, SNegz, USNz, SUegz, USUz,
$      SDegz, USDz
common/sfmixing_susy/thetat,thetab,thetatau,thetac,thetas,thetamu,
$      thetau,thetad,thetae
common/mu_mz/ murgemz
common/rgeopt_mz/mt_mz, mb_mz, mtau_mz
common/runningew/MWsq_mz,MZsq_mz
common/hzV/ delta1,delta2
common/mu_rge/mufrge
common/runningmass_susy/MT_susy, MB_susy, Mtau_susy
common/maflag/flag_bmu
```

External Routines used:

```
EXTERNAL completerun, runtomz,iterate,rewsbcor, coratmz, lhaout
```

BUGS:

SEE ALSO:

14 SuSeFLAV/softspectrumb.f

[Functions]

NAME:

softspectrumb

SYNOPSIS:

Subroutine to generate Susy spectrum.

FUNCTION:

THIS PROGRAM CALCULATES THE MASSES AND MIXINGS IN THE SOFT SECTOR FOR A GIVEN SPARTICLE MASSES AT LOW ENERGIES. THIS PARAMETERS CAN BE EITHER OUTPUT FROM RGE OR DIRECT INPUTS. AT PRESENT, IT HAS MAINLY SLEPTONIC AND SNEUTRINO PART ALONG WITH CHARGINO AND NEUTRALINO PARTS IN THE BASIS WHERE CHARGED LEPTONS ARE CONSIDERED DIAGONAL.

Higgs Spectrum added. Last Modified : 26/01/10.

INPUTS:

```

tanbeta = value of the tanbeta being used.
mSLRG   = (3 X 3) real mass matrix of left-handed sleptons (L)
mSERG   = (3 X 3) real mass matrix of right-handed sleptons (E^c)
AERG    = (3 X 3) real mass matrix of leptonic A-parameters.
M1tz    = low-energy (~M_Z) value of parameter M1
M2tz    = low-energy (~M_Z) value of parameter M2
mur     = low-energy value of the mu-parameter either through REWSB
          or as a free parameter.

```

RESULT:

```

SUEgg = 6 eigenvalues (lr-stop,lr-scharm,lr-sup) of UP-Squark mass matrix.
USU = (6 X 6) real orthogonal matrix such that,
      USU*MSU*Transpose[USU] = Diag[MSU].
SUeg = 6 singular values (descending order) of UP-Squark mass
      mass matrix. All positive.

SDegg = 6 eigenvalues (lr,lr,lr) of Down-Squark mass matrix.
USD = (6 X 6) real orthogonal matrix such that,
      USD*MSD*Transpose[USD] = Diag[MSD].
SDeg = 6 singular values (descending order) of Down-Squark mass
      mass matrix. All positive.

Slegg = 6 eigenvalues (lr,lr,lr) of slepton mass matrix.
USL = (6 X 6) real orthogonal matrix such that,
      USL*MSL*Transpose[USL] = Diag[MSL].
SLeg = 6 singular values (descending order) of slepton mass
      mass matrix. All positive.

SNegg = 3 eigenvalues (ascending order) of sneutrino mass matrix.
USN = (3 X 3) real orthogonal matrix such that
      USN*mSN*Transpose[USN] = Diag[MSN].
SNeg = 3 singular values (descending order) of sneutrino mass matrix.

ON = (4 X 4) orthogonal matrix such that
      ON.MNeut.Transpose[ON] = Diag[MNeut]
Neg = 4 singular values (descending order) of the Neutralino mass matrix.

OCR, OCL = (2 X 2) orthogonal matrices such that
      MChar = Transpose[OCR].Diag[MChar].OCL
Ceg = 2 singular values of the Neutralino Mass Matrix

AOK = Tells us whether all the diagonalising routines have run alright
      or not. Without the Higgs spectrum, AOK should be 10 on output,
      if everything goes well.

```

EXAMPLE:

```

subroutine softspectr(tanbeta,mSQRG,mSDRG,mSURG,AURG,ADRG,vev1,
$      vev2,mSLRG,mSERG,AERG,yuRG,yeRG,ydRG,M1tz,M2tz,mur,SUegg,USU,
$      SUeg,SDegg,USD,SDeg,SLegg,USL,SLeg,SNegg,USN,SNeg,ON,Neg,OCR,
$      OCL,Ceg,AOK,MT_susy,MB_susy,Mtau_susy,mh1mz,mh2mz,mh0sq,
$      mh0sq,mhpmsq,ma0sq,Neuevi,ONL,ONR)

```

NOTES:

ALL Masses and Parameters are in GeV.

Lapack is required.

Note that Lapack returns singular values as $A = U \text{Diag}[A] \text{Transpose}[V]$ or $\text{Transpose}[U] A V = \text{Diag}[A]$ which is transpose of the conventions of Mathematica as well as our conventions. (See notes). Our conventions coincide with that of HN. Also compare with that of Haber-Kane.

BUGS:

Possibly there are no bugs in this subroutine.

SEE ALSO:

15 SuSeFLAV/spectrumtl.f/completerun

[Functions]

NAME:

Subroutine completerun

SYNOPSIS:

Runs RGEs and computes tree level physical masses
for MSSM parameters.

FUNCTION:

This subroutine integrates MSSM RGEs and computes low energy spectrum at msusy.

INPUTS:

vevin	- vev at MZ
yuin	- (3x3) up type yukawa matrix
ydin	- (3x3) down type yukawa matrix
yein	- (3x3) matrix yukawa for leptons
alph1in	- $g_1^2/(16 \pi^2)$ at MZ
alph2in	- $g_2^2/(16 \pi^2)$ at MZ
alph3in	- $g_3^2/(16 \pi^2)$ at MZ
mur	- μ at mz
bmur	- $b\mu$ at mz
msusy	- susy breaking scale
prnstat	- Print control
itcount	- Rge iteration count

RESULT:

```

murge      - RGE output: \mu at M_{susy} scale
bmurge    - RGE output: b_\mu at M_{susy} scale
newtbeta   - Ratio of vev at msusy from rge running.
flags      - flags problem with rge running, if any.

Calculated tree level masses are stored in common blocks
common/softout_mat/mSQRG,mSURG,mSDRG,AURG,ADRG,
$      AERG,ANURG,mSLRG,mSERG, mSNURG,ON,OCL,OCR,MChar, MNeut
common/rgeoutput_susy/ mh1mz,mh2mz,M1tz,M2tz,M3tz,
$      alph1,alph2,alph3,vev1,vev2,yuRG,ydRG,yeRG
common/sparticles_susy/SUegg,SDegg,SLegg,SNegg,Neg,Ceg,
$      mh0sq,mhu0sq,mhpmsq,mA0sq

```

EXAMPLE:

```

subroutine completerun(msusyold,vevin,yuin,ydin,yein,
$      alph1in,alph2in,alph3in,mur,bmur,murge,bmurge,prnstat,
$      check,newtbeta,msusynew,mursq,try,flags,runum,itcount)

```

NOTES:

Common Blocks used:

```

common/mu_rge/mufrge
common/loops/ lopt,rhn
common/sminputs/ mbpole, mtaupole, Mtpole
common/mssminputs/ m0, m12, m10, m20, sgnmu, tanbeta, a0
common/mssmrhn/ MR1,MR2,MR3,ue3, Ynui
common/charinputs/case, model
common/rgeinput_high/ MX, M1X,M2X,M3X,mh10,mh20,
$      mQ0,mU0,mD0,mE0,mL0,mNU0
common/softout_mat/mSQRG,mSURG,mSDRG,AURG,ADRG,
$      AERG,ANURG,mSLRG,mSERG, mSNURG,ON,OCL,OCR,MChar, MNeut
common/rgeoutput_susy/ mh1mz,mh2mz,M1tz,M2tz,M3tz,
$      alph1,alph2,alph3,vev1,vev2,yuRG,ydRG,yeRG
common/sparticles_susy/SUegg,SDegg,SLegg,SNegg,Neg,Ceg,
$      mh0sq,mhu0sq,mhpmsq,mA0sq
common/soft_mat_susy/ mSL1, SLeg, USL, SNeg, USN, SUeg, USU,
$      SDeg, USD
common/runningmass_susy/MT_susy, MB_susy, Mtau_susy

```

External Routine used:
EXTERNAL MSSMRUN,mutreelevel,softspectrum

BUGS:

SEE ALSO:

16 SuSeFLAV/spectrumtl.f/runtomz

[*Functions*]

NAME:

Subroutine runtomz

SYNOPSIS:

Runs RGEs from msusy to MZ and computes tree level physical masses for MSSM parameters.

FUNCTION:

This subroutine integrates MSSM RGEs from msusy to MZ and computes low energy spectrum at msusy.

- * INPUTS

MX	- Reference scale, 10^{19} (GeV)
msusy	- susy breaking scale.
mu_conv	- Converged value of μ at msusy.
bmu_conv	- Converged value of b_μ at msusy.

RESULT:

- | | |
|------------|--|
| murgemz | - RGE output: μ at M_z scale |
| bmurgemz | - RGE output: b_μ at M_z scale |
| newtbetamz | - Ratio of vev at MZ from rge running. |
| flags | - flags any problem with the running |

Calculated tree level masses at MZ are stored in common blocks
`common/rgeoutput_MZ/ mh1mzz,mh2mzz,M1tmz,M2tmz,M3tmz,`
`$ alph1MZ,alph2MZ,alph3MZ,vev1mz,vev2mz,yumz,yemz`
`common/sparticles_MZ/SUeggz,SDeggz,SLeggz,SNeggz,Negz,Cegz,`
`$ mh0sqz,mhu0sqz,mhpmsqz,mA0sqz`
`common/softout_mat_mz/mSQRGz,mSURGz,mSDRGz,AURGz,ADRGz,`
`$ AERGz,ANURGz,mSLRGz,mSERGz, mSNURGz,ONz,OCLz,OCRz,`

```
$      MCharz, MNeutz
common/soft_mat_mz/ mSL1z, SLegz, USLz, SNegz, USNz, SUegz, USUz,
$      SDegz, USDz
common/rgeopt_mz/mt_mz, mb_mz, mtau_mz
```

EXAMPLE:

```
SUBROUTINE runtomz(try,MX,msusy,mu_conv,bmur_conv,
$      murgemz,bmurgemz,newtbetamz,flags)
```

NOTES:

Common Blocks used:

```
common/mssminputs/ m0, m12, m10, m20, sgnmu, tanbeta, a0
common/rgeoutput_MZ/ mh1mzz,mh2mzz,M1tmz,M2tmz,M3tmz,
$      alph1MZ,alph2MZ,alph3MZ,vev1mz,vev2mz,yumz,ydmz,yemz
common/sparticles_MZ/SUeggz,SDeggz,SLeggz,SNeggz,Negz,Cegz,
$      mh0sqz,mhu0sqz,mhpmsqz,mA0sqz
common/softout_mat_mz/mSQRGz,mSURGz,mSDRGz,AURGz,ADRGz,
$      AERGz,ANURGz,mSLRGz,mSERGz, mSNURGz,ONz,OCLz,OCRz,
$      MCharz, MNeutz
common/soft_mat_mz/ mSL1z, SLegz, USLz, SNegz, USNz, SUegz, USUz,
$      SDegz, USDz
common/rgeopt_mz/mt_mz, mb_mz, mtau_mz
common/runningew/MWsq_mz,MZsq_mz
```

External routines used:

```
EXTERNAL MSSM_MZ, softspectrum
```

BUGS:

SEE ALSO:

17 SuSeFLAV/SuSemain.f

[*Functions*]

NAME:

```
subroutine SuSemain
```

SYNOPSIS:

Main routine for running SuSeFLAV.

FUNCTION:

Computes 1-loop corrected Supersymmetric particle spectrum for a given set of mSUGRA/NUHM/CNUM inputs. Also, the routine computes branching ratios and decay rates for rare lfv processes.

INPUTS:

prnstat	-	Print Control. 1= print statements
Mg1	-	high energy input for bino
Mg2	-	high energy input for wino
Mg3	-	high energy input for gluino

Other relevant input parameters are stored in common block
 common/sminputs/ mbpole, mtaupole, Mtpole
 common/loops/ lopt,rhn
 common/mssminputs/ m0, m12, m10, m20, sgnmu, tanbeta, a0
 common/mssmrhn/ MR1,MR2,MR3,ue3, Ynui
 common/charininputs/case, model

RESULT:

errge - if any error is encountered errge =1 else =0.
 Output is written in slha.out

EXAMPLE:

```
SUBROUTINE SuSeFLAV(prnstat,mq20, mq30, mu20, mu30, md20, md30,
$      ml20,ml30, me20,me30, mn20,mn30,Mg1,Mg2,Mg3,errge)
```

NOTES:

Common blocks used:
 common/sminputs/ mbpole, mtaupole, Mtpole
 common/loops/ lopt,rhn
 common/mssminputs/ m0, m12, m10, m20, sgnmu, tanbeta, a0
 common/mssmrhn/ MR1,MR2,MR3,ue3, Ynui
 common/charininputs/case, model
 common/rgeinput_high/ MX, M1X,M2X,M3X,mh10,mh20,
\$ mQ0,mU0,mD0,mE0,mL0,mNU0
 common/softout_mat/mSQRG,mSURG,mSDRG,AURG,ADRG,

```

$      AERG,ANURG,mSLRG,mSERG, mSNURG,ON,OCL,OCR,MChar, MNeut
common/rgeoutput_susy/ mh1mz,mh2mz,M1tz,M2tz,M3tz,
$      alph1,alph2,alph3,vev1,vev2,yuRG,ydRG,yeRG
common/rgeoutput_MZ/ mh1mzz,mh2mzz,M1tmz,M2tmz,M3tmz,
$      alph1MZ,alph2MZ,alph3MZ,vev1mz,vev2mz,yumz,ydmz,yemz
common/sparticles_susy/SUegg,SDegg,SLegg,SNegg,Neg,Ceg,
$      mh0sq,mhu0sq,mhpmsq,mA0sq
common/soft_mat_susy/ mSL1, SLeg, USL, SNeg, USN, SUeg, USU,
$      SDeg, USD
common/qcd_cor/mbmzdrbar,mbMZmsbar
common/sparticles_MZ/SUeggz,SDeggz,SLeggz,SNeggz,Negz,Cegz,
$      mh0sqz,mhu0sqz,mhpmsqz,mA0sqz
common/soft_mat_mz/ mSL1z, SLegz, USLz, SNegz, USNz, SUegz, USUz,
$      SDegz, USDz
common/softout_mat_mz/mSQRGz,mSURGz,mSDRGz,AURGz,ADRGz,
$      AERGz,ANURGz,mSLRGz,mSERGz, mSNURGz,ONz,OCLz,OCRz,
$      MCharz, MNeutz
common/rgeopt_mz/mt_mz, mb_mz, mtau_mz
common/lfvindex/delta
common/mutaup/rrstaumu,USLsrt,USLTsrt
common/gauge/alph,Gf,alphas

External routines:
external rgeit

```

BUGS:

SEE ALSO:

18 susyflav/mssmrge.f

[Functions]

NAME:

mssmrge

SYNOPSIS:

In this subroutine we write all the mssm renormalization group equations, including the flavor mixing in the squark and slepton sector.

FUNCTION:

Computes the numerical values of all the mssm rge at a given energy scale

INPUTS:

yy(126)	- Initial values for all RGEs
t	- energy scale

RESULT:

yy(126) - RGE output at a scale t

EXAMPLE:

```
subroutine mssmrge(t,yy,dydx)
```

NOTES:

The notation we use closely follows that of Martin and Vaughn PRD50(1994)2282 and Ibarra and Simonetto JHEP04(2008)102.

Note that alpha1, alpha2, alpha3 in the following are further normalised by a "4 pi" factor.

Remember all the yukawa matrices are also normalised by this "4 pi x 2" factor. thus : $y_u(i,j) = [1/(4 \pi x 2)] (y_u(i,j))$; where y_u = yukawa in the lagrangian and $y_u ==$ yukawa in the program.

Also remember that all the A-parameters and the soft breaking masses are also scaled/normalised by the "4 pi x 2" factor.

```

dydx(1)-dydx(3) : yu(1,1) - yu(1,3)
dydx(4)-dydx(6) : yu(2,1) - yu(2,3)
dydx(7)-dydx(9) : yu(3,1) - yu(3,3)

dydx(10)-dydx(12) : yd(1,1) - yd(1,3)
dydx(13)-dydx(15) : yd(2,1) - yd(2,3)
dydx(16)-dydx(18) : yd(3,1) - yd(3,3)

dydx(19)-dydx(21) : ye(1,1) - ye(1,3)
dydx(22)-dydx(24) : ye(2,1) - ye(2,3)
dydx(25)-dydx(27) : ye(3,1) - ye(3,3)
dydx(28)-dydx(30) : ynu(1,1) - ynu(1,3)
dydx(31)-dydx(33) : ynu(2,1) - ynu(2,3)
dydx(34)-dydx(36) : ynu(3,1) - ynu(3,3)

```

```

dydx(37)-dydx(39) : au(1,1) - au(1,3)
dydx(40)-dydx(42) : au(2,1) - au(2,3)
dydx(43)-dydx(45) : au(3,1) - au(3,3)

dydx(46)-dydx(48) : ad(1,1) - ad(1,3)
dydx(49)-dydx(51) : ad(2,1) - ad(2,3)
dydx(52)-dydx(54) : ad(3,1) - ad(3,3)

dydx(55)-dydx(57) : ae(1,1) - ae(1,3)
dydx(58)-dydx(60) : ae(2,1) - ae(2,3)
dydx(61)-dydx(63) : ae(3,1) - ae(3,3)
dydx(64)-dydx(66) : anu(1,1) - anu(1,3)
dydx(67)-dydx(69) : anu(2,1) - anu(2,3)
dydx(70)-dydx(72) : anu(3,1) - anu(3,3)
dydx(73)-dydx(75) : mq(1,1) - mq(1,3)
dydx(76)-dydx(77) : mq(2,2) - mq(2,3)
dydx(78)           : mq(3,3)

dydx(79)-dydx(81) : mu(1,1) - mu(1,3)
dydx(82)-dydx(83) : mu(2,2) - mu(2,3)
dydx(84)           : mu(3,3)

dydx(85)-dydx(87) : md(1,1) - md(1,3)
dydx(88)-dydx(89) : md(2,2) - md(2,3)
dydx(90)           : md(3,3)

dydx(91)-dydx(93) : ml(1,1) - ml(1,3)
dydx(94)-dydx(95) : ml(2,2) - ml(2,3)
dydx(96)           : ml(3,3)

dydx(97)-dydx(99) : me(1,1) - me(1,3)
dydx(100)-dydx(101) : me(2,2) - me(2,3)
dydx(102)           : me(3,3)
dydx(103)-dydx(105) : mnu(1,1) - mnu(1,3)
dydx(106)-dydx(107) : mnu(2,2) - mnu(2,3)
dydx(108)           : mnu(3,3)

dydx(109)           : mh1
dydx(110)           : mh2
dydx(111)           : mu
dydx(112)           : b_mu

dydx(113)-dydx(118) : m_neutrino(3x3)_symmetric
dydx(119)-dydx(121) : aplh3-alpha1
dydx(122)-dydx(124) : m1t-m3t

```

BUGS:

SEE ALSO:

`smrge`, `odeint`

19 susyflav/smrg.f

[*Functions*]

NAME:

Subroutine `smrge`, `smrgemt`

SYNOPSIS:

In this subroutine we write all the standard model renormalization group.

FUNCTION:

Computes the numerical values of all the sm rge at a given energy scale

INPUTS:

<code>yy(31)</code>	- Initial values for all RGEs
<code>t</code>	- energy scale

RESULT:

`yy(31)` - RGE output at a scale `t`

EXAMPLE:

```
subroutine smrge(t,yy,dydx)
subroutine smrgemt(t,yy,dydx) - SM rge running without top
```

NOTES:

The notation we use closely follows that of Arason, castano et al, PRD46(1192)3945.

Note that alpha1, alpha2, alpha3 in the following are further normalised by a "4 pi " factor.

Remember all the yukawa matrices are also normalised by this "4 pi x 2" factor. thus : $y_u(i,j) = [1/(4 \pi x 2)] (y_u(i,j))$; where $y_u = \text{yukawa}$ in the lagrangian and $y_u == \text{yukawa}$ in the program.

Also remember that all the A-parameters and the soft breaking masses are also scaled/normalised by the "4 pi x 2" factor.

```

dydx(1)-dydx(3) : yu(1,1) - yu(1,3)
dydx(4)-dydx(6) : yu(2,1) - yu(2,3)
dydx(7)-dydx(9) : yu(3,1) - yu(3,3)

dydx(10)-dydx(12) : yd(1,1) - yd(1,3)
dydx(13)-dydx(15) : yd(2,1) - yd(2,3)
dydx(16)-dydx(18) : yd(3,1) - yd(3,3)

dydx(19)-dydx(21) : ye(1,1) - ye(1,3)
dydx(22)-dydx(24) : ye(2,1) - ye(2,3)
dydx(25)-dydx(27) : ye(3,1) - ye(3,3)
dydx(28)           : alph3
dydx(39)           : alph2
dydx(30)           : alph1
dydx(31)           : vev

```

BUGS:

SEE ALSO:

`smrge`, `odeint`